

October 2008

C905 Cyber-shot™

Your Imaging phone





Preface

Purpose of this document

This White paper will be published in several revisions as the phone is developed. Therefore, some of the headings and tables in this document contain limited information. Additional information and facts will be forthcoming in later revisions.

The aim of this White paper is to give the reader an understanding of the main functions and features of this phone.

People who can benefit from this document include:

- Operators
- · Service providers
- Software developers
- Support engineers
- Application developers

This White paper is published by:

Sony Ericsson Mobile Communications AB, SE-221 88 Lund, Sweden

www.sonyericsson.com/

© Sony Ericsson Mobile Communications AB, 2008. All rights reserved. You are hereby granted a license to download and/or print a copy of this document.

Any rights not expressly granted herein are reserved.

First edition (October 2008) Publication number: 1210-2553.4 This document is published by Sony Ericsson Mobile Communications AB or its local affiliated company, without any warranty*. Improvements and changes to this text necessitated by typographical errors, inaccuracies of current information or improvements to programs and/or equipment, may be made by Sony Ericsson Mobile Communications AB at any time and without notice. Such changes will, however, be incorporated into new editions of this document. Printed versions are to be regarded as temporary reference copies only.

*All implied warranties, including without limitation the implied warranties of merchantability or fitness for a particular purpose, are excluded. In no event shall Sony Ericsson or its licensors be liable for incidental or consequential damages of any nature, including but not limited to lost profits or commercial loss, arising out of the use of the information in this document.

Sony Ericsson Developer World

On www.sonyericsson.com/developer, developers will find documentation and tools such as phone White papers, Developers guidelines for different technologies, SDKs and relevant APIs. The Web site also contains discussion forums monitored by the Sony Ericsson Developer Support team, an extensive Knowledge Base, Tips & Tricks, example code and news.

Sony Ericsson also offers technical support services to professional developers. For more information about these professional services, go to the Sony Ericsson Developer World Web site.

Document history

Change history		
2008-06-17	Version 1	First version
2008-07-21	Version 2	Data transfer speeds updated
2008-07-29	Version 3	WLAN technical data updated
2008-10-24	Version 4	Camera information updated

Contents

Product overview	5
Key features	6
Images	10
	11
	12
Technologies in detail	
Functions and features	14
Facts and figures	
Technical specifications	
General technical data	
Performance and technical characteristics	
USSD technical data	
GPRS technical data	
SIM AT services supported	34
Entertainment	39
Audio and Video	39
Java™	41
Imaging/Messaging	41
8.1 Megapixel camera	41
Video telephony	43
Images	
Supported character set	
Short Messaging Service	
Enhanced Messaging Service	
Multimedia Messaging Service	
Email client technical data	
A-GPS	
A-GPS technical data	
Connectivity	
Bluetooth™ wireless technology technical data	
WLAN technical data	
OMA Data Synchronization (SyncML™) technical data	
Microsoft® Exchange ActiveSync®	52
Web browser technical data	
Client Provisioning	
Client Frovisioning	
Abbreviations	58
Related information	62
Documents	
Links	
Trademarks and acknowledgements	

Product overview

C905 Cyber-shot™ is a slider phone that catches consumers' eyes through its innovative design, a retractable active lens cover with premium material and easy to use high quality technology. Being a Cyber-shot phone, the core pillars building up the experience of C905 Cyber-shot™ are never miss a shot, ease of use and share your experiences.

Features include:

- 8.1 megapixel camera with auto focus, face detection, Xenon flash and Smart contrast.
- Easy-to-use horizontal digital camera menu with illuminated icons for settings shortcuts.
- Dual microphones for stereo sound when recording video.
- Photo fix to improve an under-exposed photo immediately.
- 2.4-inch QVGA scratch resistant mineral glass screen.
- Automatic blog creator
- The ability to share images using mobile blogging.
- · GPS (Global Positioning System).
- Support for A-GPS (Assisted GPS).
- Video blogging.
- Web browser supporting HTML.
- Dynamic Web pointer for Web browsing.
- PictBridge[™] to print photos directly on a printer.
- The latest in 3G/HSPDA/EDGE technology for voice and video telephony.

- Wi-FiTM.
- Slide shows with music, transitions and more.
- 3D gaming.
- · Web feeds.
- · Web feeds ticker in standby.
- FM radio with RDS and track identification.
- A stereo headset and USB cable provided in the kit.
- A memory card reader for Memory Stick Micro™ (M2™) memory cards.
- Motion gaming

5

- Exchange ActiveSync®
- Accelerometer to support auto-rotated browsing and UI, and motion gaming
- · TV out in VGA format

Key features

8.1 Megapixel camera

The main camera is 8.1 megapixel and includes auto focus, an image and video stabiliser, 16x digital zoom, Photo flash, BestPic™, Auto rotate, Face detection, smart contrast and Photo fix. All this means high quality photos. The Photo flash can be used as video light when recording videos. The camera is protected by a lens cover. The horizontal user interface allows for easier camera handling. A photo can be shared as a picture message, email message or blog with friends or family. Photos can also be transferred to another phone or computer using any available transfer method, such as Bluetooth™ wireless technology or USB cable.

Video telephony

Video telephony lets you share moments with friends and family as they happen or save them to share later. You can also use video telephony to see others while talking to them. Video telephony takes people connecting to the next level and is the next best thing to being there in person.

TrackID™

TrackID™ enables the user to identify a track playing on the built-in radio, or a track playing in the room. A few seconds of the song is sampled, the phone connects to an online database, which identifies the song and returns title, artist and album information.

Stereo widening

The Stereo Widening effects improve the sound experience when listening to music through a stereo Bluetooth headset, external stereo speakers or a stereo portable handsfree.

2.4-inch QVGA scratch resistant mineral glass screen

The large 2.4-inch (240x320 pixels) full graphic QVGA 262k colour screen enhances viewing, facilitating high-quality multimedia and entertainment.

GPS (Global Positioning System)

With the GPS and location based services such as preloaded Google Maps™ for mobile and a free three-month trial version of Wayfinder Navigator™, you can find out where you are and how to find your way. The GPS supports geo tagging. When a photo is taken, it is tagged with geographic data, meaning that the location where the photo was taken can be shown on a map.

BestPic[™]

A unique function for Sony Ericsson camera imaging. Taking a single photo or even a burst of photos does not always catch the moment, which may have been just before or just after the camera key was pressed. BestPicTM is designed to solve this problem. Press the camera key half way down and the camera starts capturing photos. Press the key fully down, and seven photos appear automatically. The photos range from left (just before pressing the camera key fully down) to centre (camera key fully down) to right (just after pressing the camera key fully down). The centre photo is the default photo, but not necessarily the best one. Browse the photo series and save the best photos.

Auto rotate

Capturing a portrait photo with a horizontal camera, usually results in a photo which must be rotated manually when viewed later, in the phone. Auto rotate is a new feature, which enables C905 Cyber-shot™ to register how the phone is oriented when the photo is taken, whether it is held in portrait or landscape

6

mode. This information is saved with the photo. When viewed, the photo is automatically rotated and presented with the same orientation as it was originally taken.

Video camera

The camera captures a video recording and saves it in the phone or on a memory card. A video clip can be shared as a picture message or email with friends and family or using any available transfer method, such as Bluetooth™ wireless technology. The phone supports QVGA size video recording.

Web feeds

A built-in RSS (Really Simple Syndication) Reader is used in combination with the Internet browser. When browsing, frequently updated content such as news headlines or podcasts can be received as feeds.

Web feeds ticker

News headlines you subscribe to can be shown in standby using Web feeds.

Wi-Fi™

Access the Internet by connecting to Wi-Fi™ networks. Browse the Internet at home (personal networks) or in public access zones (hot spots). Standards supported are 802.11b and 802.11g.

HTML Web browser support

Browse the Internet and look at Web sites in a different way with Access NetFront™ 3.4 – an HTML browser which supports a complete Web standard suite.

Landscape browsing support

View Web pages in landscape mode.

Mobile blogging

Send photos and video clips using the Internet to show on your personal blog, allowing people easy access to view and comment on your photos and video clips.

Photo tags

Navigate through your captured photos and thousands of downsized photos transferred from your computer. View captured photos and video clips in an intuitive timeline view. Play animated slide shows with music and different moods. Tag your photos to find them faster. The built-in sensor in the camera ensures that all photos are rotated correctly.

PictBridge™ - Camera printing

Print photos from the phone using the USB cable directly to a printer, without a computer or photo editing software.

TV out support

TV out can be used to show and share your photos on TV. Photos will be shown in VGA size. The TV-Out Cable ITC-60 (sold separately) is necessary to connect your phone to the TV.

Push email

The phone supports push email, a method of pushing new email messages automatically to mobile devices. Push email increases mobile email usability by delivering email in the background (similar to SMS or MMS), eliminating the need for the user to manually check for new email.

7

Media

A unique Sony Ericsson media experience. All media can be accessed directly from the desktop. Navigate seamlessly through captured photos and video clips, pictures, photo tags, music, videos and more.

Music player

Located in Media. Play downloaded music and audio. The navigation system enables you, for example, to browse through your favourite tracks and create simple playlists.

Video player

Located in Media. Play saved and downloaded video clips.

Sony Ericsson Media Manager

Music, photo and video clip management software is available on the CD included in the kit. Transfer music, video clips and photos to and from your phone. Search for and select music on your computer or audio CDs and convert your existing audio tracks to formats suitable for mobile use before transferring them to your phone. You can also subscribe to feeds such as video and music podcasts.

PlavNow™ 5.0

A unique and easy-to-use direct-link for downloading ringtones, full track music, games, themes and wall-papers. PlayNowTM offers best-selling content for mobile download. Users can preview content before purchase. Users have access to a catalogue of millions of tracks from both international and local labels.

By combining the PlayNow[™] catalogue with unique applications like TrackID[™] users are presented with a My TrackID[™] list and TrackID[™] Charts by country, created by TrackID[™] users around the world. These charts are based on what songs other users are searching for and want to hear the most. PlayNow[™] supports MP3 and Windows Media DRM file formats for music.

PlayNow™ uncut

PlayNow™ uncut is a promotional site for introducing new and developing artists. PlayNow™ uncut includes full track music, videos, gig schedules and information about the stars of tomorrow. PlayNow™ uncut provides consumers with the possibility to discover new music which otherwise might pass them by. At the same time, the site offers artists and songwriters the opportunity to have their music heard by millions of consumers.

Gaming

Gaming is a very popular feature in mobile phones. Shake or tilt the phone to control gaming functions. Two action keys have been added to intensify the experience. With Java™, users can download new games and skill levels to further enhance their entertainment experience.

Java™

Download additional applications which are information- and entertainment-based. This gives users a chance to personalise the functions and features in their phones, and developers the opportunity to create new applications. Java Platform 8.4.0 (JP-8.4.0), supports a range of new Java programming features including instant messaging (chat) and presence-based functionality, handling banking, payment transactions, user identification and authentication through secure encryption technology.

Bluetooth™ wireless technology

Several devices (simultaneous Bluetooth™ wireless technology connections) can be connected up to 10 metres (33 feet) away using Bluetooth wireless technology. For example, when the phone rings, it can be answered with a Bluetooth headset, and images can be sent to another phone at the same time. Several

mobile phones can take part in a Bluetooth wireless technology-supported game and the phone and a computer can exchange data such as images, video clips, vCards, music files and calendar data. Bluetooth wireless technology version 2.0 and Enhanced Data Rate (EDR) is supported.

Bluetooth™ audio streaming

Listen to audio in compatible devices. By connecting a Bluetooth Advanced Audio Distribution Profile (A2DP) compatible accessory, such as a stereo Bluetooth headset or a Bluetooth music receiver, you can enjoy high quality stereo audio streaming wirelessly from the phone. Many A2DP accessories also support the Bluetooth Audio Video Remote Control Profile (AVRCP) allowing you to control the player in the phone using the accessory interface.

USB 2.0 mass storage

When connecting the phone to a computer using the provided USB cable, the memory in the phone appears on the computer screen as a removable disk along with other disks and drives in the computer. You can then quickly and easily drag and drop items such as images, documents, music and video clips between folders in the phone and the computer.

Media Transfer Protocol (MTP)

With Media Transfer Protocol you can transfer media files and synchronise playlists when the phone is connected to the computer using the USB cable. It is possible to use MTP in Media transfer mode or Phone mode. MTP is supported by Sony Ericsson Media Manager, Windows Media Player 11 and higher in Windows XP and Windows Vista™.

Personal Information Management (PIM)

Stay up-to-date with everyday events by synchronizing phone contacts, calendar appointments, tasks and notes in the phone with similar programs in a computer. The USB cable which comes with the phone, or the built-in Bluetooth wireless technology feature can be used together with the synchronization software which is available on the CD in the kit or can be downloaded from www.sonyericsson.com/support. Smart search your contacts and call list for phone numbers or names from standby. Predefined speed dial numbers can be quickly sent out from standby.

Common Internet File System (CIFS)

The Common Internet File System enables file transfer to and from your phone. The phone acts as a file server which allows you to copy and move files between your PC and the server. You can use this feature when connected using Wi-FiTM, the USB cable or the Bluetooth wireless technology connection.

Digital Living Network Alliance (DLNA™)

The phone has a built-in DLNA™ server that connects to the home network through Wi-Fi™. Other DLNA devices connected to the same home network can access, view and play images and music saved on your phone. A compatible DLNA device can be a computer, TV or PLAYSTATION®3.

Images















Technologies in detail

This chapter includes short descriptions of the technologies available in this product compared to other Sony Ericsson products.

Functions and features

The following includes short descriptions of the technologies available in C905 Cyber-shot™, K850 and C902 Cyber-shot™.

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
3D games	Yes	Yes	
3G enabled	Yes	Yes	
Activity menu (multi-tasking) The user can easily handle missed calls, new text and picture messages, task reminders, shortcuts and get quick access to favourite Internet bookmarks	Yes with enhanced functionality for background applications	Yes with enhanced functionality for background applications	Yes with enhanced functionality for background applications
Alarm clock	Yes	Yes	Yes
Set up to five individual times for single or recurring weekly alarms			
Auto rotate	Yes	Yes	Yes
The photo appears as a landscape or portrait photo, as it was originally taken			
Backlight	Yes	Yes	Yes
White backlight to illuminate the phone screen			
Battery	BST-38 3.6 V, 930 mAh, Lithium Polymer	BST-38 3.6 V, 930 mAh, Lithium Polymer	BST-38 3.6 V, 930 mAh, Lithium Polymer
Battery charging time	At least 90% charged within 2 hours. Fully charged within 2.5 hours	At least 90% charged within 2 hours. Fully charged within 2.5 hours.	At least 90% charged within 2 hours. Fully charged within 2.5 hours
BestPic™	Yes	Yes	Yes
Enhance photo taking by automatically capturing a range of 7 photos ranging from before to after a camera key press. Select the best photo to catch the moment. You can also save more than one photo.			
Select BestPic [™] speed BestPic [™] with light	Yes No	Yes No	Yes Yes
Bluetooth™ audio streaming	Yes	Yes	Yes
Listen to audio in compatible devices			

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
Bluetooth™ audio video remote control	Yes	Yes	Yes
Control music player functions from a Bluetooth™ accessory, and control the volume in the accessory from the phone			
Bluetooth™ PAN	Yes	Yes	Yes
Connect the phone to Internet using Bluetooth [™] wireless technology			
Bluetooth™ wireless technology	Yes	Yes	Yes
Wireless connectivity between devices within a range of up to 10 metres (33 feet). Support for specification of the Bluetooth System, version 2.0 and EDR			
Business card exchange	Yes	Yes	Yes
Exchange contact information			
Calculator	Yes	Yes	Yes
Calendar	Yes	Yes	Yes
Calendar with day, week and month views and reminders			
Call list	Yes	Yes	Yes
View calls made and received			
Camera	8.1 Megapixel	5.0 Megapixel	5.0 Megapixel
Camera retractable lens cover	Yes	Yes	Yes
Open the cover and camera functionality starts automatically			
Camera auto focus	Yes	Yes	Yes
The camera automatically focuses on the subject in a focus area in the screen/viewfinder			
Camera face detection	Yes	No	Yes
The camera brings an off-centre face into focus			
Camera file browser	Yes	Yes	Yes
Browse the photo folder without leaving the camera function			
Camera flash	Yes	Yes	Yes

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
Camera image stabiliser	Yes	Yes	Yes
Photo and video image stabiliser functionality. If available, use to keep the image steady			
Camera key	Yes	Yes	Yes
A dedicated camera key			
Camera keys on top	Yes	Yes	Yes
When the camera is used in horizontal mode, the side keys with camera functionality are on top, for a digital still camera feel. For photo key functionality, see also "Keys – side and other" on page 22			
Camera menu	Yes	Yes	Yes
Easy-to-use horizontal digital camera menu			
Camera mode switch	Yes	Yes	No
Use to switch between photo, video and play modes			
Camera red eye reduction	Yes	Yes	No
Camera scene modes Use predefined settings when taking photos in different environments, for example, at night or fast-moving objects	Yes Dedicated key for scenes	Yes	Yes
Camera settings bar	Yes	Yes	Yes
Settings bar with options and info texts			
Chinese input method	Yes	Yes	Yes
Chinese input methods: Text input methods based on Simplified or Traditional Chinese. Bopomofo, Pinyin or Stroke			
Circuit Switched Data			
CSD	Yes	Yes	Yes
HSCSD – a communications standard enabling GSM data transfer 14.4 Kbps.	Yes	Yes	Yes
Smart contrast	Yes	No	No
Improves detail in a photo by achieving an automatic light balance between the darker and lighter areas of your photo.			

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
Co-branding area	47.4 × 6.75 mm	Yes (size not defined)	47.4 × 6.75 mm
Code memo	Yes	Yes	Yes
A safe place to save all PIN codes and other information. To access Code memo, only one PIN code is needed			
Colour	Night Black Ice Silver Copper Gold	Luminous Green Velvet Blue Quicksilver Black	Luscious Red Swift Black
Contact photos	Yes	Yes	Yes
Add a photo to a saved contact. The picture appears on the screen when the saved contact calls			
Contacts	Yes	Yes	Yes
Phonebook with fields for name, phone, fax and instant messaging information, presence information, email address, Web site, title, company address info, personal address info and birthday			
Conference calls	Yes	Yes	Yes
Support for multiparty calling			
Connector A1 (Fast port)	Yes (side)	Yes (bottom)	Yes (side)
Content online	Yes	Yes	Yes
Downloadable pictures, games, themes, ringtones available online			
Copyright protection DRM (Digital Rights Management) features the rights and copy protection of downloaded content (audio, pictures, music tones, video clips and entertainment features such as games, Java applications etc.)	Yes, OMA DRM 1.0, 2.0 and 2.1, Microsoft DRM Janus	Yes, OMA DRM 1.0, 2.0 and 2.1, Microsoft DRM Janus	Yes, OMA DRM 1.0, 2.0 and 2.1, Microsoft DRM Janus

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
Device Management (DM)	Yes	Yes	Yes
DM utilises GPRS as a bearer (basic network connectivity needs to be in place) of the provisioning data and allows the operator to access the phone, check and send out different settings such as network connectivity (GPRS), email, MMS, Internet settings and Java™. Device Management is achieved by supporting OMA Client Provisioning 1.1 (CP) and OMA Device Management (DM) 1.2			
Digital zoom	16x for all photo sizes and video recording	16x for photos 16x for video clips 16x for video calls (on main camera) 2x for video calls (on QCIF camera)	16x for photos 16x for video clips 2x for video calls
Digital Living Network Alliance (DLNA™)	Yes	No	No
Built-in DLNA™ server that connects to the home network through Wi-Fi™			
Dual microphones	Yes	No	No
Two microphones give stereo sound to video clips recorded by the phone			
Email	Yes	Yes	Yes
Built-in email client with inbox, outbox, compose/ send and other functions			
EMS (Enhanced messaging)	Yes	Yes	Yes
Text messaging (SMS) with support for pictures and sounds			
Note: EMS is not available for operators who use unified messaging			
Exterior description			
Size mm (Length x width x thickness/thinnest)	104x 49x 18/ 19.5 (at camera lens)	103 x 48.5 x 18	108 x 49 x 10.5
External antenna connector	No	No	No
For use with an advanced car handsfree accessory			

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
Fast port	Yes	Yes	Yes
A system connector which enables faster data transfer between the phone and a computer			
File manager Folder structure storage to help save and organise pictures, sounds and other phone content	Yes, with enhanced functionality for camera	Yes, with enhanced functionality for camera	Yes, with enhanced functionality for camera
	content	content	content
Flash themes	Yes	No	No
Flight mode	Yes	Yes	Yes
All phone radio transceivers are inactivated. Flight mode starts the phone so that only certain functions are available, such as the calendar, the music player or a game. The phone may then be used in some areas, such as aeroplanes or hospitals, where full mobile phone functionality is not allowed			
Bluetooth™ wireless technology function availability in Flight mode	Yes	Yes	Yes
Wi-Fi™ function availability in Flight mode	Yes	N/A	N/A
FM radio with RDS FM radio with presets, auto and manual search. The handsfree is used as an antenna. The radio can also be used as an alarm signal	Yes, 100 kHz tuning interval	Yes	Yes
FM radio with TrackID™	Yes	Yes	Yes
Identify tracks playing on the radio			
Form factor	Slider	Monolithic Stick	Stick
Games download	Yes	Yes	Yes
Add more games to your phone			
Games embedded	Yes	Yes	Yes
Geo tagging	Yes, geo data from	No	Yes, geo data from
Photos are tagged with geo data and can be shown on a map	ĞPS		cell-id

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
Google Maps for mobile Preloaded application with support for cell-id and GPS. View satellite imagery, find locations and calculate routes	Yes	No	Yes (No built-in GPS, but support for GPS Enabler HGE-100)
GPRS	Yes	Yes	Yes
General Packet Radio Services – a communications standard enabling packet data transfer of 21.4 Kbps per time slot. Multislot class 10 supported (max 5 simultaneously)			
High Speed Data			
HSDPA - High Speed Downlink Packet Access	Yes	Yes	Yes
Icon Desktop 12	Yes	Yes	Yes
A graphic icon desktop with 12 interactive icons			
Image formats			
8 MP (3264 x2448 pixels)	Yes	No	No
5 MP (2592x1944 pixels)	Yes	Yes	Yes
3.2 MP (2048x1536 pixels)	No	No	No
3 MP (2048x1536 pixels)	Yes	Yes	Yes
2 MP (1632x1224 pixels)	No	Yes	Yes
1 MP (1280x960 pixels)	No	Yes	Yes
VGA (640x480 pixels)	Yes	Yes	Yes
Infrared port	No	No	No
A wireless connector enabling the user to connect the phone to a laptop or another infrared device in order to share pictures, synchronise calendar or use the phone as a modem			
Instant messaging (Wireless Village)	Yes	Yes	Yes
Chat – several people can take part in a mobile messaging session. Instant messaging/Wireless Village server community			

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
Internet blogging	Yes	Yes	Yes
Share over the Internet on your personal Web site. The size of uploaded photos is dependent on customizations			
Internet browser	Yes	Yes	Yes
Full HTML support, ECMA script, DOM level 1&2, CSS 1&2 etc.	Yes	Yes	Yes
Support for AJAX (Asynchronous JavaScript and XML)	Yes		Yes
Progressive download of video files.	Yes	Yes	Yes
Direct access to Bookmarks, Search Internet and Enter address	Yes	Yes	Yes
Mouse Pointer	Yes	No	Yes
Text Wrapping	Yes	No	Yes
Pan&Zoom	Yes	No	Yes
Internet security	Yes, SSL/TLS	Yes, SSL/TLS	Yes, SSL/TLS
Encrypts confidential information such as credit card and bank account numbers. Necessary for mobile banking and shopping			
Java TM	Java 2, Micro Edition	Java 2, Micro Edition	Java 2, Micro Edition
Support for J2ME™ technology	(J2ME™), Java 3D™	(J2ME TM), Java	(J2ME™), Java 3D™
Sony Ericsson Java Platform	JP-8.4	JP-8.0	JP-8.3
Support for new Java programming features including banking, payment transactions, user identification and authentication through secure encryption technology.	Yes	Yes	Yes

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
Keys - navigation and more	4 navigation keys	4 navigation keys	4 navigation keys
	3 selection keys	3 touch options	3 selection keys
	C (Clear) key	C (Clear) key	C (Clear) key
	Activity menu key	Activity menu key	Activity menu key
	End and on/off key	End key	End key
	Call key	Call key	Call key
	A and B gaming keys/ photo keys		multimedia (play/stop) on centre selection key
Keys - keypad	12 alphanumeric	12 alphanumeric	12 alphanumeric
Keys - side and other	Volume/ camera zoom key	Volume/ camera zoom key	Volume/ camera zoom key
	Camera key	Camera key	Camera key
	Camera mode key	Mode switch (photo, video, view)	
	Camera view key	Camera on/of	
		Separate on/	
Lunar calendar	Yes	Yes	Yes
A calendar system used in China and other parts of Asia. A lunar month is determined by the period required for the moon to complete its full cycle of 29.5 days and is available in Chinese phone variants			

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
Adobe™ Flash Lite™	Yes	Yes	Yes
For animated wallpapers, menus and other graphic elements			
Media	Yes	Yes	Yes
A centre for all media content with horizontal and vertical navigation. You can view photos, listen to music, watch video clips			
Media player	See Music player and Video player	See Music player and Video player	See Music player and Video player
Mega Bass™	Yes	Yes	Yes
An audio feature which enhances bass frequencies for better overall music experience			
Memory (built-in)			
Phone memory that is free to use (depending on software configuration and file content). Many applications share phone memory. The maximum amount of storage available for any one application, such as calendar entries, is affected by the amount of memory used by other applications, such as messaging, music, photos and so on	Up to 160 MB	Up to 40 MB	Up to 160 MB
Memory card reader (slot)			
A slot for inserting a micro peripheral storage device	Yes	Yes	Yes
Memory card support: Memory Stick Micro [™] (M2 [™]) SanDisk microSD [™] /Transflash [™]	Yes No	Yes Yes	Yes No
Menu layout options	Yes	No	Yes
Possibility to change the layout of the icons in the main menu			
Menu shortcuts	Yes	Yes	Yes
A function making it possible to dedicate shortcuts to the most-used phone functions			
MMS (Multimedia messaging)	Yes	Yes	Yes
Picture messaging with text and sound			

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
MMS video	Yes	Yes	Yes
Support in the phone for sending video clips using MMS			
Modem	Yes	Yes	Yes
Circuit Switched/Packet Switched Internet dial-up support			
MusicDJ™	Yes	Yes	Yes
A music composer tool with MIDI drum, guitar, keyboard, bass and brass loops in different music styles, which can be combined to create polyphonic ringtones			
Music listening time	Up to 20 hours	Up to 40 hours	Up to 25 hours
Music player 3.0	Yes	Yes	Yes
A digital music player with horizontal navigation. Play music you have transferred or downloaded. The list structure system enables you, for example, to organise favourite songs into groups and create simple playlists.			
Music tones	Yes	Yes	Yes
Music tones, also called master tones, are DRM protected music by original artists. Various digital audio formats are supported			
My time zone	Yes	Yes	Yes
Select the time zone manually by country or city			
Networks			
3G/HSDPA	UMTS/HSDPA 850, 1900, 2100	UMTS 850, 1900, 2100	UMTS/HSDPA 2100
GSM/GPRS/EDGE	GSM (R99) 850, 900, 1800, 1900, E- GSM 900	GSM (R99), 850, 900, 1800, 1900, E- GSM - 900	GSM/EDGE 850, 900, 1800, 1900 MHz

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
Notes	Yes	Yes	Yes
Make notes of things to remember. A note can be shown in standby			
OMA Data Synchronization (SyncML)	Yes	Yes	Yes
A device communications standard that enables remote synchronization between devices	OMA DS 1.2 OMA DS 1.1.2	OMA DS 1.2 OMA DS 1.1.2	OMA DS 1.2 OMA DS 1.1.2
OTA settings	Yes	Yes	Yes
Internet, email and other settings can be sent over the air to the phone	OMA CP 1.1	OMA CP 1.1	OMA CP 1.1
Photo light (built-in)	See Camera flash	See Camera	See Camera flash
When lighting conditions are poor, activate the picture light			
PhotoDJ™	Yes	Yes	Yes
A drawing tool in the phone where existing photos can be altered			
Photo fix	Yes	Yes	Yes
Improves an under-exposed photo by calculating and adjusting the light balance			
PictBridge™	Yes	Yes	Yes
Transfer images from the phone via the USB cable directly to a printer, without a computer or photo editing software			
Picture gallery	Yes	Yes	Yes
A thumbnail image gallery where sections of several photos can be viewed at the same time	Use photo tags	Use photo tags	Use photo tags
PlayNow™ (direct link)	Yes	Yes	Yes
Listen to music before you purchase and download it to your phone			
PlayNow™ Games (direct link)	Yes	Yes	Yes
Download and purchase games straight from the phone desktop			
Polyphonic voices	72	72	72

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
Powersave	Yes		Yes
default setting for display light			
Predictive text input	Yes	Yes	Yes
Push email	Yes	Yes	Yes
RSS reader	See Web feeds	See Web feeds	See Web feeds
Screen			
Type: Size: Resolution:	Full graphical 2.4 inches 240x320 pixels	Full graphical 2.2 inches 320x240 pixels	Full graphical 2.0 inches 320x240 pixels
Technology: Colours displayed together:	TFT, QVGA 262,000 (18 bit)	TFT, QVGA 262,000 (18 bit)	TFT, QVGA 262,000 (18 bit)
Backlight colour:	White	White	White
Screen saver	Yes	Yes	Yes
Settings download (Ready to run) Set up functions that require a connection to the Internet such as the Internet browser and picture messaging. This function runs in the setup wizard or can also be chosen in the Settings menu. This function is not included in the setup wizard for customised phones		Yes	
Shake control	No	No	No
Shake control for music and gaming			
SIM card lock The possibility to protect the SIM card with a four-digit to eight-digit PIN code	Yes	Yes	Yes
Smart search	Yes	Yes	Yes
Search for numbers and contacts from standby by using the number keys. Smart filter and smart search by names in contacts list by entering some keys. Call or send messages from a filtered list of search results.			
SMS long (Text messaging)	Yes	Yes	Yes
Concatenated SMS text messaging			

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
Sleep mode	Yes	Yes	Yes
A power-saving feature that minimises the battery power consumed when the phone is in standby			
Sony Ericsson Remote Update Service	Yes	Yes	Yes
Download the latest operator-approved software, over the air, for your mobile phone			
Sony Ericsson Update Service	Yes	Yes	Yes
Connect the phone to an Internet-connected computer, download the latest operator-approved software from the Web site, www.sonyericsson.com/support and update the mobile device			
Sound recorder	Yes	Yes	Yes
A recording device in the phone that can record voice messages or other sounds			
Speakerphone	Yes	Yes	Yes
Speed dialling	Yes	Yes	Yes
Allocate contacts in the phone book to specific keys on the keypad			
Standby time	Up to:	Up to:	Up to:
GSM UMTS	400 hours 350 hours	400 hours 350 hours	380 hours 360 hours
Status view	Yes	Yes	Yes
The screen shows the network being used, the time and other status information			
Stereo microphone	Yes	No	Yes
Stereo speakers	No	No	No
Stopwatch	Yes	Yes	Yes
SVG Tiny	Yes	Yes	Yes
Scalable Vector Graphics for impressive animated wallpapers, menus and other graphic elements			
Synchronization PC	Yes	Yes	Yes
Synchronise and share phone content with a computer			

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
Talk time	Up to:	Up to:	Up to:
GSM UMTS	9 hours 3.5 hours	9 hours 3.5 hours	9 hours 4 hours
Tasks	Yes	Yes	Yes
Keeps track of important things you have to do			
Themes	Yes	Yes	Yes
Phone menu texts and background graphics			
Timer	Yes	Yes	Yes
Set the phone to alert after a specific time			
TrackID™			
Music recognition	Yes	No	Yes
Text search for artist, album, track, lyrics etc.	Yes	No	Yes
UMTS	Yes	Yes	Yes
USB connectivity support	Yes	Yes	Yes
Connect the phone to a computer using the USB cable provided	USB 2.0 Hi-Speed	USB 2.0 Hi-Speed	USB 2.0 Hi-Speed
USB ethernet emulation	Yes	Yes	Yes
Connect to the Internet using the phone or the computer			
Vibrating alert	Yes	Yes	Yes
The phone vibrates when a call comes in			
Video blogging	Yes	Yes	Yes
Share video clips over the Internet on your personal Web site. The size of uploaded video clips is dependent on customizations			
Video call camera	No	Yes	Yes
Video call talk time	Target Up to 2 hours 30 minutes	Target Up to 2 hours 30 minutes	Target Up to 2 hours 30 minutes

Feature	C905 Cyber- shot™	K850	C902 Cyber- shot™
VideoDJ™	Yes	Yes	Yes
Create video sequences by combining different clips and adding music and images			
Video player	Yes	Yes	Yes
Play video clips you have transferred or downloaded. Transfer video clips to another phone or a computer using an available transfer method			
Video streaming	Yes	Yes	Yes
Real-time streaming of video clips, for example, live cam. Media can also be downloaded and saved in the phone memory			
Video telephony	Yes	Yes	Yes
When you make a video call, the other party can be seen on the screen. The service requires UMTS/WCDMA			
Viewfinder	Yes	Yes	Yes
When using the camera, a photo can be previewed before it is captured			
Voice control	Yes	Yes	Yes
Voice answer, reject and call. Assign voice commands to items in the phonebook. When a call is made, the voice command can be used instead of pressing keys			
Voicemail	Yes	Yes	Yes
Support for voicemail operator service including automatic answering and message recording			
Web feeds	Yes	Yes	Yes
Frequently updated content delivered as feeds via a Web site, for example, news headlines in the browser			
Web feeds ticker	Yes	Yes	Yes
View news headers in standby			
Weight	136 g	118 g	106.6 g
Wi-Fi™	Yes	No	No
Connect the phone to the digital home network or Internet using Wi-Fi™ 802.11b or 802.11g			

Facts and figures

This chapter offers readers a detailed listing of all the technical data relating to the product. Comprehensive descriptions of performance and technical characteristics are presented in table format for quick and easy access.

Technical specifications

General technical data

System	Quad-band GSM Release 5 recommendations, GSM 850, GSM 900, e-GSM 900, GSM 1800, GSM 1900 Tri band UMTS/HSDPA 850, 1900, 2100 supported
Speech coding	HR, FR, EFR, AMR, supported where available, for high speech quality.
GSM SIM/ UMTS USIM/SIM card	GSM SIM - 3GPP TS 51.011; UMTS USIM - 3GPP TS 31.102; UMTS ISIM - 3GPP TS 31.103. Small plug-in card, 1.8 V and 3 V.
Memory	Up to 160 MB internal (depending on software configuration/file content) plus extra slot for supported memory cards.
Data transfer speeds	Up to 7.2 Mbps (downlink, HSDPA, cat 8) Up to 384 Kbps (uplink, WCDMA R99)

Performance and technical characteristics

Property	WCDMA 2100
Frequency range (MHz)	TX: 1920–1980 RX: 2110–2170
Channel spacing	5 MHz with 200 kHz channel rasters
Number of channels	277
Modulation	QPSK (WCDMA R99) QPSK/16 QAM (HSDPA)
πι	10 ms (WCDMA R99) 2 ms (HSDPA)
TX phase accuracy	Error Vector Magnitude: <17.5%
Duplex spacing	190 MHz
Frequency stability	+/-0.1 ppm
Voltage operation (nominal)	3.6 V
Transmitter RF power output	24 dBm Class 3 (0.25 W peak)
Transmitter Output impedance	50 ohm
Transmitter spurious emission (according to specification)	< -36 dBm up to 1 GHz < -30 dBm over 1 GHz (according to 3GPP™ spec.)

Property	WCDMA 2100		
Receiver RF sensitivity	Better than -106.7 dBm	@ 12.2 kbps CS voice	
Receiver RX bit error rate	< 0.1%		
Property		GSM 850	GSM 900/ E-GSM 900
Frequency range (MHz)		TX: 824-849 RX: 869-894	TX: 880-915 RX: 925-960
Channel spacing		200 kHz	200 kHz
Number of channels		124 Carriers *8 (TDMA)	174 Carriers *8 (TDMA)
Modulation		GMSK	GMSK
TX phase accuracy		< 5° RMS phase error (burst)	< 5° RMS phase error (burst)
Duplex spacing		45 MHz	45 MHz
Frequency stability		+/- 0.1ppm	+/- 0.1ppm
Voltage operation (nominal)		3.6 V	3.6 V
Transmitter RF power output	ut	33 dBm Class 4 (2 W peak)	33 dBm Class 4 (2 W peak)
Transmitter output impedar	nce	50 ohm	50 ohm
Transmitter spurious emissi specification)	ion (according to	< -36 dBm up to 1 GHz < -30 dBm over 1 GHz	< -36 dBm up to 1 GHz < -30 dBm over 1 GHz
Receiver RF sensitivity		Better than -04 dBm	Better than -02 dBm
Receiver RX bit error rate		< 2.4%	< 2.4%
Property		GSM 1800	GSM 1900
Frequency range (MHz)		TX: 1710-1785 RX: 1805-1880	TX:1850-1910 RX:1930-1990
Channel spacing		200 kHz	200 kHz
Number of channels		374 Carriers *8 (TDMA)	299 Carriers *8 (TDMA)
Modulation		GMSK	GMSK
TX Phase Accuracy		< 5° RMS Phase error (burst)	< 5° RMS Phase error (burst)
Duplex spacing		95 MHz	80 MHz
Frequency stability		+/-0.1ppm	+/-0.1ppm
Voltage operation (nominal)		3.6 V	3.6 V
Transmitter RF power output	ut	30 dBm Class 1 (1 W peak)	30 dBm Class 1 (1 W peak)

Property	GSM 1800	GSM 1900
Transmitter output impedance	50 ohm	50 ohm
Transmitter spurious emission (according to specification)	< –30 dBm	< –30 dBm
Receiver RF sensitivity	Better than -102 dBm	Better than -102 dBm
Receiver RX bit error rate	< 2.4%	< 2.4%

USSD technical data

Feature	Support	
USSD support	GSM Phase 1/2 (cross-phase compatibility)	
Mode support	UI-mode supportedSAT initiated USSD supported	
UI-mode details	 It is possible to scroll the text up and down in USSD messages It is possible to highlight embedded numbers and take actions accordingly 	

GPRS technical data

Property	Support
Compatible GPRS/EDGE and SMG specifications	Release 99 according to ETSI specification
Data rates GPRS (per time slot)	Coding scheme
	CS-1: 9 Kbps
	CS-2: 13,4 Kbps
	CS-3: 15,6 Kbps
	CS-4: 21,4 Kbps (network-dependent).
Data rates EDGE (per time slot)	Modulation & coding scheme (MCS)
	MCS-1 (GMSK): 8.0 Kbps
	MCS-2 (GMSK): 11.4 Kbps
	MCS-3 (GMSK): 14.8 Kbps
	MCS-4 (GMSK): 17.6 Kbps
	MCS-5 (8-PSK): 22.4 Kbps
	MCS-6 (8-PSK): 29.4 Kbps
	MCS-7 (8-PSK): 44.8 Kbps
	MCS-8 (8-PSK): 54.4 Kbps
	MCS-9 (8-PSK): 59.2 Kbps
Medium Access Modes	Dynamic allocation
Support of Packet Control Channels (PBCCH/PCCCH)	Yes
Network operation mode	NOM I, II, III

Property	Support
Support of GPRS/CS combined procedures	Yes
Network control mode	NC0 and NC2
Support of access in 2 phases	Yes
Support of PRACH on 11 bits	Yes
Support of GPRS re-selection C31/C32	Yes
Support of static and dynamic addressing	Yes
Support of power control uplink and downlink	Uplink = yes, downlink is a network feature
Support of ciphering algorithms	GEA1, GEA2
Support of compression algorithms	Yes, V42bis and IP header compression
Mode of operation	Class B and Class C modes of operation supported
R Reference point	 Physical layer: Support of RS232 PPP is supported as L2 layer in the R reference point Authentication algorithms PAP, CHAP supported
IP connectivity	 PDP type IP is supported IP termination in mobile or TE (laptop, PDA) is supported
PDP context	 10 PDP context descriptions saved in the phone PDP context description is edited via application in the phone AT-command or via OTA Simultaneous PDP contexts are supported, maximum 4
SIM	GPRS aware, as well as non-GPRS aware, SIM cards are supported
AT commands	Some of the supported commands: AT+CGDCONT - DEFINE PDP CONTEXT AT+CGEQREQ - Quality of Service Profile (REQUESTED) AT+CGEQMIN - Quality of Service Profile (Minimum Acceptable) AT+CGATT - PACKET DOMAIN SERVICE ATTACH OR DETACH AT+CGACT - PDP CONTEXT ACTIVATE OR DEACTIVATE AT+CGDATA - ENTER DATA STATE For more information, see www.sonyericsson.com/developer

SIM AT services supported

Service	Mode	Support
CALL CONTROL BY SIM		Yes
MO SMS CONTROL		Yes

Service		Mode	Support
DATA DOWNLOAD TO SIM		Cell Broadcast SMS	Yes Yes
DISPLAY TEXT		Text of up to 240 characters (120 UCS2 coded).	Yes
	bit 1:	0 = normal priority	Yes
		1 = high priority	Yes
	bit 8:	0 = clear message after a delay	Yes
		1 = wait for user to clear message	Yes
GET INKEY		General: The GET_INKEY requires that the user confirms his/her choice	Yes
	bit 1:	0 = digits (0-9, *, # and +) only	Yes
		1 = alphabet set	Yes
	bit 2:	0 = SMS default alphabet	Yes
		1 = UCS2 alphabet	Yes
	bit 3:	0 = character sets defined by bit 1 and bit 2 are	Yes
		 enabled 1 = character sets defined by bit 1 and bit 2 are disabled and the Yes/No response is requested 	Yes
GET INPUT		General: No. of hidden input characters	252
	bit 1:	1: 0 = digits (0-9, *, # and +) only 1 = alphabet set	Yes
			Yes
	bit 2:	0 = SMS default alphabet 1 = UCS2 alphabet	Yes
			Yes
	bit 3:	0 = ME may echo user input on the display 1 = user input not to be revealed in any way (see note)	Yes
			Yes
	bit 4:	0 = user input to be in unpacked format 1 = user input to be in SMS packed format	Yes
			Yes
	bit 8:	0 = no help information available	Yes
		1 = help information available	Yes
LAUNCH BROWSER			Yes
MORE TIME			Yes
PLAY TONE			Yes
POLLING OFF			Yes
POLL INTERVAL			Yes

Service		Mode	Support
PROVIDE LOCAL INFORMATION		'00' = Location Information (MCC, MNC, LAC and Cell Identity)	Yes
		'01' = IMEI of the ME	Yes
		'02' = Network Measurement results	Yes
		'03' = Date, time and time zone (DTTinPLI)	Yes
		'04' =Language setting	Yes
		'05' =Timing advance	Yes
REFRESH		General: The reset option requests the user to wait while the phone restarts	Yes
		'00' = (U)SIM Initialization and Full File Change Notification	Yes
		'01' = File Change Notification	Yes
		'02' = (U)SIM Initialization and File Change Notification	Yes
		'03' = (U)SIM Initialization	Yes
		'04' = (U)SIM Reset	Yes
		'05' = USIM Application Reset	Yes
		'06' = 3G Session Reset	Yes
SELECT ITEM			Yes
SEND DTMF			Yes
SEND SHORT MESSAGE	bit 1:	0 = packing not required 1 = SMS packing by the ME required	Yes Yes
SEND SS			Yes
SEND USSD			Yes

Service	Mode	Support
SET UP CALL	General: Capability configuration Set-up speech call CallParty Subaddress DTMF support	Yes No Yes
_	'00' = set up call, but only if not currently busy on another call	Yes
	'01' = set up call, but only if not currently busy on another call, with re-dial	Yes
	'02' = set up call, putting all other calls (if any) on hold	Yes
	'03' = set up call, putting all other calls (if any) on hold, with re-dial	Yes
	'04' = set up call, disconnecting all other calls (if any)	Yes
	'05' = set up call, disconnecting all other calls (if any), with re-dial	Yes
SET UP EVENT LIST	'00' = MT call	Yes
	'01' = Call connected	Yes
	'02' = Call disconnected	Yes
	'03' = Location status	Yes
	'04' = User activity	Yes
	'05' = Idle screen available	Yes
	'06' = Card reader status	Not Applicable
	'07' = Language selection	Yes
	'08' = Browser termination	Yes
	'09' = Data available	Yes
	'OA' = Channel status	Yes
SET UP IDLE MODE TEXT		Yes, 1 row of text is supported
SET UP MENU		Yes
TIMER MANAGEMENT		Yes
OPEN CHANNEL		Yes
CLOSE CHANNEL		Yes
RECEIVE DATA		Yes

Service	Mode	Support
SEND DATA		Yes
GET CHANNEL STATUS		Yes

User Interaction with SIM AT

BIP - Open Channel

A user confirmation is displayed with the default text "Open channel" when no alpha identifier is present. Alpha identifier text replaces the default text when the Alpha Identifier is present & not null. No user indication is provided (transparent mode) when alpha identifier is present and null.

Display text

Text of up to 240 characters (120 UCS coded) is supported.

Text clearing times are 5-20 seconds with a 60-second time-out limit for the user to clear the text. 'Key' responses:

- 'End key' Proactive session terminated by user
- 'Back' Backward move in proactive session.

MSK clears the screen if the command is performed successfully.

Get inkey

Prompt for a one-character input. Pressing 'Ok' without entering a character gives warning message "Text too short". 'Key' responses:

- · 'C' clears current character.
- 'End key' terminates the proactive session.
- 'Back' Backward move in the proactive session.
- 'OK' Command performed successfully.

Get input

Prompt for character input. The phone will refuse to accept further input when maximum response length is exceeded. UI Maximum Response lengths:

• Digits Only – 160 characters.

- SMS default alphabet characters 160 characters.
- Hidden Characters (digits only) 20 characters.

'Key' responses:

- 'C' clears current character.
- 'End key' terminates the proactive session.
- 'Back' Backward move in proactive session.
- 'OK' Command performed successfully.

Select item

Scroll to highlight item for selection. 'Key' responses:

- Navigational key press down Scroll down list.
- Navigational key press up Scroll up list.
- End key terminates proactive session.
- 'Back' Backward move in proactive session.
- 'OK'- Command performed successfully.

Send short message

Alpha Identifier text is displayed, if it is present. Otherwise, there is no user indication if the customization for default text is not enabled. If the customization for default text is enabled, and there is no Alpha Identifier, default message "Sending message" is displayed. Default responses are "Message failed" or "Message sent" for the customization enabled case with no Alpha Identifier.

'Key' responses:

End key or 'Back' ends the proactive session.

Set up call

If you are on a call when the commands 'Set up Call', 'Putting all other calls on hold' are sent, the user will see the "Let SIM card setup call" user confirmation text. If 'OK' is pressed the current call will be put on hold and the new call set up. If the phone is on a call when the command 'Set Up Call, disconnecting all other calls' is sent, the user will

see the 'Let SIM card setup call' user information text. If the 'OK' key is pressed the current call will be disconnected and the new call set up.

Set up menu

Incorporates a SIM Application Toolkit Menu Item into the ME's main menu structure.

If an Alpha Identifier is supplied in the Set Up Menu command, this is used as the SIM AT entry in the ME's main menu. If null alpha identifier is supplied and several items are found in the menu, the default title "ONLINE SERVICES" is used. If the SIM AT Menu Item is selected by pressing 'Select', all the items sent in the Set Up Menu command will be available for selection, in the same way as the Select Item command.

Entertainment

Audio and Video

File types	Formats	Extensions
Audio	3GP	.3gp
(All listed audio file formats are	AAC	.aac
supported ringtone file formats)	MP4	.mp4
	M4A	.m4a
	MP3	.mp3
	AMR	.amr
	AMR-WB	.awb
	WAV	.wav
	SMF (Standard MIDI File format)	.mid
	RealAudio® 8	.ra, .rm
	iMelody	.imy
	XMF (Mobile XMF supported)	.xmf, .mxmf
	WMA	.wma
Video (including audio part)	MP4 (Video: MPEG4 or H.264, Audio: AAC or AAC+ or eAAC+) 3GPP™ (Video: MPEG4, H.263 or H.264, Audio: AMR-NB, AMR-WB, AMR-WB+, AAC, AAC+ or	.mp4
	eAAC+)	.3gp
	RealVideo® 8, 9, 10	.rv, .rm
	WMV	.wmv, .asf
Streaming transport	RTSP according to 3GPP™	
Video encoding	H.263 Profile 0, Level 10 MPEG-4 Visual Simple Profile Level 3	
Audio encoding	AMR-NB AAC (for video recording only)	

File types	Decoder format	Supported in file format
Video decoding	MPEG-4 Visual Simple Profile	3GP/MP4
	H.264 Baseline Profile	3GP/MP4
	H.263 Profile 0	3GP
	RealVideo 8, 9, 10	RealVideo 8, 9, 10
	VC-1 (WMV9)	WMV
Audio decoding	MPEG-1/2/2.5, audio layer 3	MP3
-	AAC	3GP/AAC/MP4/M4A
	AAC+	3GP/AAC/MP4/M4A
	eAAC+	3GP/AAC/MP4/M4A
	AMR-NB	3GP/AMR
	AMR-WB	3GP/AMR/AMR-WB
	AMR-WB+	3GP
	RealAudio Gecko/Sipro	RealAudio 8
WMA version	WMA version 2,7,8: Class 1	WMA
	WMA version 9: Level 3	WMA
	WMA Pro (profile M0a)	WMA
	General MIDI (GM)	SMF
	GML	SMF
	SP-MIDI	SMF, XMF
	DLS (Mobile DLS supported)	XMF
	Linear/A-law/μ-law PCM	WAV

Java™

Feature	Functionalities
Java™ Platform, Micro Edition	 JSR-75 PDA Optional Packages for J2METM JSR-82 Bluetooth Wireless Technology API JSR 118 MIDP 2.0 JSR-120 Wireless Messaging API JSR-205 Wireless Messaging API 2.0 JSR-135 Mobile Media API 1.1 JSR 139 CLDC 1.1 JSR-172 J2METM Web Services Specification JSR-177 Security and Trust Services API for J2METM JSR-179 Location API (built-in GPS) JSR-180 SIP API for J2METM JSR-184 Mobile 3D Graphics API for J2METM JSR 185 JavaTM Technology for the Wireless Industry JSR-211 Content Handler API JSR-226 SVG API for J2METM JSR-229 Payment API JSR-234 Advanced Multimedia Supplements JSR-238 Mobile Internationalization API JSR-239 OpenGL ES JSR-248 Mobile Services Architecture JSR-256 Mobile Sensor API (accelerometer) Nokia UI Extension API
Java 3D	 Mascot Capsule Micro3D Version 3 JSR-239 OpenGL ES JSR-184 Mobile 3D Graphics API for J2ME™

Imaging/Messaging

8.1 Megapixel camera

Digital still camera (DSC)	
True colour	Yes
Digital zoom	Main camera: 16x zoom
Photo fix	Improves an under-exposed photo by calculating and adjusting the light balance
Still camera settings bar	
Shoot modes	Normal, Smart contrast, BestPic™, Panorama, Frames

Scenes	Auto, Twilight landscape, Twilight portrait, Landscape, Portrait Beach/Snow, Sports, Document	
Photo sizes (resolution)	8 MP (3264 x2448 pixels) 5 MP (2592x1944 pixels) 3 MP (2048x1536 pixels) VGA (640x480 pixels) Note: MP = Megapixel	
Focus	Auto, Face detection, Macro, Infinite	
Flash	Off, Auto, Red-eye reduction	
ISO setting	ISO Auto	
Self-timer	Off, On	
Metering mode	Normal, Spot	
White balance	Auto, Daylight, Cloudy, Fluorescent, Incandescent	
Effects	Off, Black & white, Negative, Sepia, Solarise	
Still camera setup		
Picture quality	Normal, Fine	
Auto focus light	Off, Auto	
BestPic™ speed	Slow, Fast	
Review	Off. On	
Image stabiliser	Available, if enabled, when Xenon Flash is disabled	
Add position (geo tagging)	Off, On	
Save to memory	Memory card or phone memory	
Auto rotate	Off, On	
Shutter sounds	Yes	
Reset settings	Yes	
Reset file number	Yes	
Video recorder		
Video size (resolution)	QVGA 320x240 pixels	
Frame rate	30 fps (frames per second)	
Digital zoom		
Video camera settings bar		
Video clip length	For video clips, For picture messages	
Light	Off, On	
Night mode	Off, On	

Self-timer	Yes, same as camera
Microphone	Off, On
Metering mode	Yes, same as camera
White balance	Yes, same as camera
Effects	Yes, same as camera
Video camera setup	
Stabiliser	Off, On
Review	Off, On
Save to memory	Memory card or phone memory
Reset settings	Yes, same as camera
Reset file number	Yes, same as camera

Video telephony

Photo sizes (resolution)	QCIF (176x144 pixels) SQCIF (128x96 pixels)
Digital zoom	16x zoom
Night mode	Yes
White balance	Auto
Brightness	Yes
Video coding	H.263 MPEG-4 Visual Simple Profile Level 0
Audio coding	AMR

Images

Images can be shared using a Bluetooth wireless technology connection, MMS, email message, computer file transfer or memory card.

The image size is limited by the amount of free RAM.

Formats	Details	
JPEG	 ISO/IEC JPEG Baseline DCT Progressive DCT Non-differential nlimited size 	
GIF	 87a, 89a, support for interlacement, animation and transparency Unlimited size 	
ВМР	Windows® bitmap format	
PNG	Unlimited size	
SVG	SVG Tiny 1.2	
WBMP	Wireless bitmapUnlimited size	

Supported character set

Decoding text (Incoming MM	S)	
US-ASCII	UTF-16	
ISO-8859-1	KOI8-R	
ISO-8859-2	GB2312	
Windows-1251	GB 18030	
ISO 10646 (UCS-2)	GB 13000	
UTF-7	BIG-5	
UTF-8		
Coding Text (Outgoing MMS)		
UTF-8		

Short Messaging Service

Feature	Support
SMS Service Centre Number It is possible to pre-load the SMS Service Number	
Pictures	It is possible to insert a picture or an icon into the text message. EMS compliant mobile phones will be able to see the picture correctly
Reply to messages	It is possible to reply to received messages by SMS, MMS, voice message and email
Input methods:	Predictive writing and multitap

Feature	Support
Copy and paste words	Yes
Teaching of predictive words that are not in the predictive dictionary	Yes
Options when creating a message:	
Save a sent message in a "Sent items" folder	Yes
Insert a line in the message	Yes
Assign a validity period to the message	Yes
Use predefined messages	Yes
Options when receiving a message:	
Reply to the sender	Yes
Forward the message	Yes
Save the message on the SIM card	Yes
Get delivery time and date	Yes
Options with the previously sent message:	
Delivery report of the message	Yes (if requested when sending)
Forward the message	Yes
Save the message on the SIM card	Yes
Know the remaining capacity storage	Yes, $>$ 95% full warning, capacity on SIM when saving to SIM
Options with the previously received message:	
Reply to the sender	Yes
Save the message in the inbox	Yes
Forward the message	Yes
Know the remaining capacity storage	Yes, $>$ 95% full warning, capacity on SIM when saving to SIM
Supported ways for replying to a received SMS:	
Via SMS, MMS, voice message, email	Yes
Via phone call (set up a call to the number contained in the message body)	Yes
Via Web browser (go to the Web address contained in the message body)	Yes
Via USSD session	No

Feature	Support
Print via infrared	No
Possibility to enable the user to send a text message to a list of recipients	Yes
Possibility to write an email address as a recipient address	Yes, if email gateway is present
SMS storage	In the phone memory, on the SIM card, or on memory card
Capacity	Up to 1,000 messages
Nokia Picture Messaging	Yes

Enhanced Messaging Service

Enhanced Messaging Service (EMS) according to the standard 3GPP™ TS 23.040 v4.3.0, with the addition of the ODI feature from 3GPP™ TS 23.040 v5.0.0 10 It is possible to: • See how many short messages an EMS message con-
It is possible to:
•
sists of before sending it. Choose whether to send the message or not after writing it.
 A signal is heard once all parts of the message have been received or when a time-out occurs. It is possible to re-use the content of an EMS message. Sounds, pictures, and animations can be inserted in a new message, if the object is not protected using ODI.
A receipt is received in the phone when all parts of a concatenated message have been delivered if a delivery report is requested when it is being sent
It is possible to add pictures, animations and sounds to an EMS message
Chimes high, chimes low, ding, tada, notify, drum, claps, fanfare, chords high, chords low

Feature	Support
Melodies	 It is possible to: Receive (always), send using EMS (if not copyright protected). Download melodies and commercial tunes from the Web.
WBMP	Yes
Picture sizes	16x16, 32x32 pixels, variable size in black and white
Pictures	 It is possible to: Edit pictures using PhotoDJ™. Receive (always), send using EMS (if not copyright protected). Download pictures from the Web.
Animations	There is support for the following animations: Angry, Crying, Flirty, Happy, Kiss, Sad, Tongue, Wow, Confused, Devil, Glasses, Indifferent, Laughter, Sceptical and Wink, as defined in 3GPP™ TS 23.040 v4.3.0. It is possible to send and receive animations
TP-PID field value given by the phone before sending an EMS message	0x00
EMS storage capacity	Up to 1,000 messages

Multimedia Messaging Service

Feature	Support
MMS/CSD parameters and MMS/GPRS parameters placement	 MMS is bound to an MMS profile. A MMS profile is bound to a Data account. A data account contains either CSD parameters or GPRS parameters and possibly proxy settings
Possibility to pre-configure the MMS parameters in the factory	MMS/CSD: YesMMS/GPRS: Yes
Possibility to configure the MMS parameters by OTA provisioning	MMS/CSD: YesMMS/GPRS: Yes
Possibility for all the parameters from the parameters set to be OTA provisioned at the same time	MMS/CSD: YesMMS/GPRS: Yes
Possibility for only one parameter, in the set of parameters, to be OTA provisioned	MMS/CSD: No MMS/GPRS: No
Supplier indication of realized interoperability tests between its MMS User Agent and MMS Relay/Server from other suppliers	Yes

Feature	Support
Support of a standard procedure for OTA provisioning of MMS parameters	OMA Client Provisioning 1.1
Functionalities that the user is able to set during message composition:	 Message subject Message priority Email recipient address Message Cc, Bcc recipient(s) address(es) Delivery report request MSISDN recipient address Validity period
From where can the user insert multimedia elements into multimedia messages:	File Manager Photo album Camera Contacts Calendar Task Note Browser (vBookmark) VideoDJ TM PhotoDJ TM PhotoDJ TM Sound recorder
Possibility for sent messages to be memorised into a folder in phone memory	Yes
Actions that the user can perform after message retrieval:	 Reply to the sender of the message SMS/MMS Reply to the sender and to Cc, Bcc people SMS/MMS Forward the message Delete the message Save message in a dedicated folder Call the sender of a message Save item Mark as unread Details
Multimedia codecs/formats supported for audio	AAC, AMR, MPEG Layer 3, Real 8, AWB, WAV, MP4, MIDI, iMelody, 3GPP™, XMF, M4A, WMA
Multimedia codecs/formats supported for video	MPG4, 3GPP™, SDP, Real 8, WMV
Multimedia codecs/formats supported for image	JPEG, GIF87, GIF89A, PNG, SVG, WBMP, BMP
Supported formats for message presentation:	 Message body plus attachments (email presentation) SMIL version as described in OMA MMS IOP document version 1.2
Maximum message size that can be handled by the phone	Content Class and Creation mode are applied. Maximum size can also be customised
Maximum number of objects supported in a message	30 objects is standard. It is possible to increase the number through configuration

Feature	Support
Maximum text size	5,000 characters/text
Storage capacity	Up to 500 messages

Email client technical data

Feature	Support
Bearer type (IP)	Yes
Bearer type GSM Data (IP)	Yes, GPRS and HSCSD
Character sets	 ISO: ISO-8859-1, ISO-8859-2, ISO-8859-5, ISO-8859-7, ISO-8859-9, ISO-8859-10, ISO-8859-11 Windows: Windows-1251, Windows-1252, Windows-1254, Windows-1255, Windows-1258 US-ASCII Unicode: UTF-7, UTF-8, UTF-16 Japanese: Shift_JIS, ISO-2022-JP Cyrillic: KOI8-R Simplified Chinese: GB2312, GB18030 Traditional Chinese: Big5
OTA provisioning solution	OMA Client Provisioning 1.1
Protocols	POP3 and IMAP4
Push email	IMAP IDLE (extension of IMAP4 Rev1), OMA Email Notification 1.0 and scheduled checking, Exchange ActiveSync® (EAS)
Secure email	SSL/TLS, both port methods (POPS/IMAPS) and STARTTLS
HTML mail	Yes (tags removed)
Thumbnailed image attachments	Yes
Message management	User selectable inbox size, save messages to Memory Stick, arrange messages by date, size and Email address
ESMTP	Yes
Background sending	Yes

A-GPS

A-GPS technical data

Feature/Dimension	Support
Standards	Control plane (3GPP™) and user plane (OMA SUPL v1.0) assistance. It is also possible to use the GPS receiver in autonomous mode without any assistance data.
OMA SUPL v1.0	 The SLP address can be configured using OMA Client Provisioning v1.1. Secure data connection for assistance data delivery.
Performance	Varies depending on geographic location and network operator support.

Connectivity

Bluetooth™ wireless technology technical data

Dimension	Support
Bluetooth™ wireless technology capability statement	This phone supports Bluetooth Specification, version 2.0 with enhanced data rate (EDR)
Bluetooth™ wireless technology profiles	Advanced Audio Distribution Profile Audio/Video Remote Control Profile Basic Imaging Profile Dial-up Networking Profile File Transfer Profile Generic Access Profile Generic Object Exchange Profile Handsfree Profile Headset Profile Human Interface Device Profile Object Push Profile Personal Area Networking Profile Phonebook Access Profile Synchronization Profile SyncML OBEX binding
Connectable devices	All products supporting Bluetooth spec. 1.1, or higher, and at least one of the profiles above

Dimension	Support
Coverage area	Varies due to radio performance between the connected devices and the occurrence of obstacles. Up to 10 metres (33 feet)
Transmission power	Class 1, typical +3 dBm or 2 mW
Frequency band	2.4 GHz - the unlicensed ISM band
Power consumption	 GSM host processor excluded: Standby, Bluetooth On mode: <0.6 mA Voice to headset (HV3 master): 11 mA (7 mA with EDR functionality, 2EV3 master). Dependent on various parameters such as if the phone is master or slave Data mode average: 27mA at 172.8 Kbps symmetrical (DH1)
Data transmission rate	 Data speed at least 800 Kbps on a Dial-up Networking connection (requires access to HSDPA network and may be limited by capacity situation on the 3G base station) Data speed typically 1.0 Mbps on an Object Push connection between two phones (in case of using similar phones and if no other Bluetooth devices are connected)

WLAN technical data

Dimension	Support
Supported standards	Wi-Fi [™] certified. The mobile phone can access the Internet using a Wireless Local Area Network instead of GPRS or 3G. When applicable, 802.11g is prioritized over 802.11b
Connectable devices	Wi-Fi™ access points
Frequency band	2.4 GHz
Data transmission rate	5 MBit/s
Security	Open Open WEP Shared WEP WPA Personal and WPA2 Personal WPA Enterprise and WPA2 Enterprise
Encryption	TKIP and AES
Power save	WMM-UAPSD
QoS	WMM

OMA Data Synchronization (SyncML™) technical data

Feature	Support for Sync ML
SyncML compliance	The phone is fully SyncML compliant, having passed SyncML Conformance testing. OMA DS 1.2 or OMA DS 1.1.2 is used depending on configuration and both are supported in Serveralerted synchronization
Basic data formats	Contacts: vCard 2.1, Calendar: vCalendar 1.0 (vEvent) Tasks: vCalendar 1.0 (vTodo) Notes: text/plain, Bookmarks:vBookmark 1.0
Possibility for operators to extend SyncML functionality	The device may be configured to include preset SyncML settings, and to control whether SyncML 1.1 or SyncML 1.2 will be used
Transport method for SyncML messages	HTTP, HTTPS, OBEX (USB, Bluetooth)
Possibility for the user to configure login parameters (for example, username and password) to access the remote database	Yes
Configuration parameters that can be entered/modified by the user	Server URL, Username, User PWD, Paths to databases (Calendar, Contacts, Notes, Tasks and Bookmarks), UserID and PWD for databases, Databases to be synchronised (On/Off), Internet profile, Synchronization interval, Server ID and Server PWD, permission to allow server-alerted synchronization and roaming options. Can be provisioned with OMA Client provisioning v1.1 and OMA Device Management v1.2
Ability to deal with multiple servers	Yes
Ability to perform conflict resolution actions	Yes

Microsoft® Exchange ActiveSync®

Feature	Support for Exchange ActiveSync
Protocol version	The phone supports version 2.5 of Microsoft Exchange ActiveSync
Supported applications	Email, Calendar, Phonebook
Transport method used	HTTP, HTTPS
Possibility for the user to configure login parameters for remote server	Yes

Feature	Support for Exchange ActiveSync
Configuration parameters that can be entered/modified by the user	Server URL, username, domain name, password, applications to sync, email message size, email attachment size, email date range, message alert sound, calendar date range, interval sync, secure connection, roaming option
Ability to perform conflict resolution	No

Web browser technical data

Feature	Support in the browser
Bookmarks	Yes, with folders and sorting supported
Bookmark Export/Import	Yes, can be sent and received using vBookmark format using Bluetooth™ wireless technology, SMS, MMS and email
Browser compliancy	The Web browser is compliant with the following standards: HTML ver. 4.01 XHTML Basic 1.0 XHTML 1.1, Module-based XHTML XHTML Mobile profile WML 1.3 Cascading Style Sheets, level 2 revision 1, CSS 2.1 Specification Wireless CSS Specification, Version 26-Oct-2001 (WAP-239-WCSS-20011026-a) ECMA-script according to specifications found at http://www.ecma-international.org/publications/standards/ Stnindex.htm ECMAScript Mobile Profile AJAX Document Object Model Level 2 (DOM 2) Scalable Vector Graphics, Mobile SVG Profile: SVG Tiny, version 1.2 For further details, see the WAP User Agent strings and profiles for Sony Ericsson mobile phones Developers guidelines at Developer World http://developer.sonyericsson.com/
Browser version	Access NetFront 3.4
Cache	Yes (size 2 MB)
Character sets *	Most standard character sets, among others UTF-8 (Default), UTF-16, USASCII, Latin1, UCS2. For updated and detailed information, see the WAP User Agent strings and profiles for Sony Ericsson mobile phones Developers guidelines at Developer World http://developer.sonyericsson.com/ * When creating pages, it is recommended to always save the page
	contents as UTF-8.
Clear cache	Yes, persistent. By user interaction, at SIM card change or master reset
Frames	Full Frame support: Frames, IFrames

Feature	Support in the browser	
Image formats and animations	GIF (interlaced and non-interlaced) WBMP, JPEG, PNG, BMP and SVG. Animated GIFs, animated SVG and Flash	
Schemes	Http:, https:, rtsp:, mailto:, smsto:, mmsto:, tel:, wtai:	
Streaming	Progressive download, RTSP, Java script controls	
Web feeds	Ticker, podcasts, enclosures, OPML import. No support for ATOM	
User agent profile		
User Agent Profiles	Yes, list of client characteristics - for example, screen size. For details, see the WAP User Agent strings and profiles for Sony Ericsson mobile phones Developers guidelines at Developer World http://developer.sonyericsson.com/	
URL sent pointing to the UA profile at the beginning of browser session	Yes. For details, see the WAP User Agent strings and profiles for Sony Ericsson mobile phones Developers guidelines at Developer World http://developer.sonyericsson.com/	
Download		
OMA download functionality	Yes	
HTTP GET solution to download content/ Uses browser for download	Yes	
Other download content	Yes. No download limit when using HTTP protocol	
Download application/product memory check	Yes	
Downloaded object solution	Yes. The user is informed where the content is saved and asked if it should be used at once or later	
UAP indication for downloading	Yes	
Other features	Yes. Save, delete, forward, use, manage	
Object formats	All formats can be downloaded and saved, but only formats supported by the phone can be used by the phone	
Resume	Yes	
Background download	Yes	
Progressive download	Yes	
Streaming	Yes	
Browser navigation		
Selection keys	Yes. Two selection keys and centre navigation key	
Separate/dedicated back or erase keys	Yes	
Display backlight on when browsing	Yes	

Feature	Support in the browser
Predictive writing	Yes
"http://" string displayed automatically when entering URLs	Not displayed but the "http://" is added automatically to the URL
"www" added automatically when entering URLs	Yes
Combined Search/Go To input field	Intelligent input field changes appearance (Search or Go to) depending on user input. "www", ".com" and other URL syntax can be used to trigger the Go To appearance
Internet network features	
Bluetooth™ wireless technology (as local connection)	Yes
Infrared (as local connection)	No
Network settings	Yes
PPP Authentication	PAP, CHAP supported
Security	HTTPS authentication TLS version 1 SSL version 3 WIM on SIM ICC X.509 certificate support, Mobile Profile WPKI OTA download of trusted certificates
USB (as local connection)	Yes
PUSH	
Content types	
Service Indication (SI)	Yes
Service Loading (SL)	Yes
Cache Operation (CO) content type	No
Session Initiation Application (SIA)	Yes
Man Machine Interface	
SI/content retrieval postponing	Yes
SI menu structure accessibility	Messaging, Inbox
SL reception warning	The user can make a choice if a dialogue is wanted or not before loading the SL
SIA reception warning	Yes
Cache size limitations	The oldest push in the inbox will be discarded

Feature	Support in the browser
Number of push messages	Depends on the size of the push messages. Around 20 push messages with a size of 1024 bytes URL and 1024 bytes Indications for Service Indication can be saved.
Push deactivate	Yes
Dynamic push menu changes	No. There are no changes in the menus when activating/deactivating push
Security	
Mechanisms for push	None
Trust with PPG	Sending a SIA is the most reliable
WSP push sessions	No
HTTP push sessions	The White List (a setting to allow push messages only from certain addresses) is supported for IP address
SMS connection-less push	The White List (a setting to allow push messages only from certain addresses) is supported for SMS Center
Denial of service/spoofing	Setting to select when to allow push messages: Always, always ask or never. There is also a setting to select whether to allow push messages from all senders or only from certain addresses (the White List)

Client Provisioning

Feature	Support
Provisioning types	OMA Client Provisioning (v1.1)
Total Parameter sets	25 (shared between the provisioning types) < or = 25 (total number of data accounts)
Parameter set list	See the Device Management v4 Developers Guideline at Developer World http:// www.sonyericsson.com
Factory pre-configuration	Yes. This also provides the possibility to lock a setting
Security mechanism	
Bearer	

Feature	Support
SMS	Uses security mechanism (SEC) methods according to OMA-WAP-ProvCont- v1_1-20050428-C (see www.openmobilealliance.o rg). For NETWPIN the user is asked to accept to install received settings. For USERPIN, USERNETWPIN and USERPINMAC the user is subsequently asked to enter a PIN code that is a shared secret between the service provider and the user
Carrier reset/provisioning	Yes, but not if the set is pre-configured in the factory and locked
SWIM	Not used for provisioning. The SWIM is only used for wireless security, both SSL/TLS connections and digital signatures
Applicative provisioning	
Preferred bearer customization	Yes
Other applications/features	Yes (MMS, Email, OMA Data Synchronization, Wireless Village, OMA Device Management, Streaming)
Technologies	
OMA Client Provisioning	Yes, Client Provisioning version 1.1
Nokia/Ericsson OTA	No
Openwave OTA	No
Other	No
Provisioning bearer	SMS

Abbreviations

ЗGPР™

3rd Generation Partnership Project

A-GPS

Assisted GPS

AAC

Advanced Audio Coding

AAC+

High Efficiency AAC v.1

AJAX

Asynchronous JavaScript and XML

AMR

Adaptive Multi Rate. Audio format for speech sounds

AMR-NB

Adaptive Multi Rate Narrow Band

AMR-WB

Adaptive Multi Rate Wide Band, a more efficient codec that supports speech with higher quality

API

Application Programming Interface

Bluetooth PAN

Bluetooth Personal Area Network

CS

Circuit Switched

CSD

Circuit Switched Data

 $DLNA^{TM}$

Digital Living Network Alliance

DRM

Digital Rights Management. Controlling copying and distribution of contents, with respect to intellectual property rights

DTMF or Touch Tone

Dual Tone Multi-Frequency signal. Codes sent as tone signals. Used for telephone banking, accessing an answering machine, etc.

EDGE

Enhanced Data Rates for GSM Evolution

e-GSM

Extended GSM. New frequencies specified by the European Radio Communications Committee (ERC) for GSM use when additional spectrum is needed (network-dependent). It allows operators to transmit and receive just outside GSM's core 900 frequency band. This extension provides increased network capability

eAAC+

High Efficiency AAC v.2

EDR

Enhanced Data Rate

EFR

Enhanced Full Rate, speech coding

EMS

Enhanced Messaging Service. Allows the user to add simple pixel pictures and animations, sounds and melodies to a text message. The EMS 3GPP™ standard also includes text formatting

ETSI

European Telecommunications Standards Institute

FM

Frequency Modulation of the (radio) carrier wave

FR

Full Rate, speech coding.

GIF

Graphics Interchange Format

GPS

Global Positioning System

GPRS

General Packet Radio Services

GSM

Global System for Mobile Communications. GSM is the world's most widely used digital mobile phone system, now operating in over 100 countries around the world, particularly in Europe and Asia-Pacific.

The GSM system family includes GSM 850, GSM 900, GSM 1800 and GSM 1900. There are different phases of roll-out for the GSM system and GSM phones are either phase 1 or phase 2 compliant

HR

Half Rate, speech coding

HSCSD

High Speed Circuit Switched Data

HSDPA

High Speed Downlink Packet Access

HTML

HyperText Markup Language

HTTP

HyperText Transfer Protocol

IrDA

Infrared Data Association

JPEG

Joint Photographer Expert Group

MIDI

Musical Instrument Digital Interface

ME

Mobile Equipment

MP

Megapixel

MP3

Short for "MPEG-1 layer 3", an audio coding scheme

MPEG4/MPG4

Moving Picture Experts Group. MPEG-4 is a standard used primarily to compress audio and visual digital data.

MT

Mobile Termination

ODI

Object Distribution Indicator

OMA

Open Mobile Alliance

OTA

Over The Air

PDA

Personal Digital Assistant

PDP

Packet Data Protocol

PIM

Personal Information Management

PNG

Portable Network Graphic

QCIF

Quarter Common Intermediate Format

RDS

Radio Data System

RSS

Really Simple Syndication

RTSP

Real Time Streaming Protocol session control.

SI

Service Indication

SL

Service Loading

SIM card

Subscriber Identity Module card – a card that must be inserted in any GSM-based mobile phone. It contains subscriber details, security information and memory for a personal directory of numbers. The card can be a small plug-in type or credit cardsized, but both types have the same functions. The phone uses the small plug-in card.

SMS

Short Messaging Service. Allows messages of up to 160 characters to be sent and received via the network operator's message centre to a mobile phone

SP-MIDI

Scalable Polyphony MIDI

SS

Supplementary Services

SSL

Secure Socket Layer

TLS

Transport Layer Security

TTI

Transmission Time Interval

UI

User Interface

UMTS

Universal Mobile Telecommunications System

URL

Uniform Resource Locator.

The global address of documents and other resources on the World Wide Web

USSD

Unstructured Supplementary Services Data

vCard

vCard automates the exchange of personal information typically found on a traditional business card, for use in applications such as Internet mail, voicemail, Web browsers, telephony applications, call centres, conferences, PIMs /PDAs, pagers, fax, office equipment and smart cards. vCard is specified by IETF

VGA

Video Graphics Array

WAV

Waveform audio format

WMA

Windows Media Audio

WMA Pro

Windows Media Audio Professional

WBMP

Wireless BitMap.
A graphic format optimised for mobile computing devices

WCDMA

Wideband Code Division Multiple Access

WML

Wireless Markup Language. A markup language used for authoring services, fulfilling the same purpose as HyperText Markup Language (HTML) does on the World Wide Web (WWW). In contrast to HTML, WML is designed to fit small handheld devices

WPA

Wi-Fi Protected Access

WWW

World Wide Web

XHTML

Extensible HyperText Markup Language

XML

Extensible Markup Language

Related information

Documents

- Sony Ericsson User guide
- Sony Ericsson FAQ

- AT Command Reference Manual
- WAP 2.0 Specifications

Links

- www.sonyericsson.com/
- www.ericsson.com/mobilityworld/
- www.midi.org
- www.extendedsystems.com
- www.gsmworld.com/
- www.bluetooth.com
- www.imc.org
- www.3gpp.org
- www.irda.org

- www.etsi.fr
- www.openmobilealliance.org
- www.imc.org/pdi/
- www.w3.org/TR/xhtml-basic/
- www.java.sun.com
- www.memorystick.org/
- www.memorystick.com/
- www.sonyericsson.com/updateservice
- www.sonyericsson.com/support

Trademarks and acknowledgements

The Bluetooth™ word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Sony Ericsson is under licence.

The Liquid Identity logo, PlayNow, BestPic, SensMe, VideoDJ, MusicDJ, TrackID and PhotoDJ are trademarks or registered trademarks of Sony Ericsson Mobile Communications AB.

WALKMAN, Mega Bass, Memory Stick Micro, Cyber-shot, M2 and Sony are trademarks or registered trademarks of Sony Corporation.

PLAYSTATION is a trademark or registered trademark of Sony Computer Entertainment, Inc.

NetFront is a trademark or a registered trademark of ACCESS Co., Ltd.

PictBridge is a trademark or registered trademark of Canon Kabushiki Kaisha Corporation.

Ericsson is a trademark of Telefonaktiebolaget LM Ericsson.

TrackID™ is powered by Gracenote Mobile MusicID™. Gracenote and Gracenote Mobile MusicID are trademarks or registered trademarks of Gracenote, Inc.

Google™ and Google Maps™ are trademarks or registered trademarks of Google, Inc.

Wayfinder and Wayfinder Navigator are trademarks or registered trademarks of Wayfinder Systems AB.

Wi-Fi is a trademark or registered trademark of the Wi-Fi Alliance.

DLNA is a trademark or registered trademark of the Digital Living Network Alliance.

Real, RealAudio, RealVideo are the trademarks or registered trademarks of RealNetworks, Inc.

MicroSD™ and Transflash™ are trademarks or registered trademarks of SanDisk Corporation.

The IrDA Feature Trademark is owned by the Infrared Data Association and used under licence there from.

XHTML™ is a registered trademark of the W3C.

Microsoft®, Windows® Vista and ActiveSync are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Adobe Flash Lite are trademarks or registered trademarks of Adobe Systems Incorporated in the United States and/or other countries.

3GPP™ is a trademark of ETSI in France and other jurisdictions.

SyncML is a trademark or registered trademark of Open Mobile Alliance Ltd.

Java and all Java based trademarks and logos are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.

End-user license agreement for Sun Java™ J2ME™:

- 1. Restrictions: Software is confidential copyrighted information of Sun and title to all copies is retained by Sun and/or its licensors. Customer shall not modify, decompile, disassemble, decrypt, extract, or otherwise reverse engineer Software. Software may not be leased, assigned, or sub licensed, in whole or in part.
- 2. Export Regulations: Software including technical data, is subject to U.S. export control laws, including the U.S. Export Administration Act and its associated regulations, and may be subject to export or import regulations in other countries. Customer agrees to comply strictly with all such regulations and acknowledges that it has the responsibility to obtain licenses to export, re-export, or import Software. Software may not be downloaded, or otherwise exported or re-exported (i) into, or to a national or resident of, Cuba, Iraq, Iran, North Korea, Libya, Sudan, Syria (as such listing may be revised from time to time) or any country to which the U.S. has embargoed goods; or (ii) to anyone on the U.S. Treasury Department's list of Specially Designated Nations or the U.S. Commerce Department's Table of Denial Orders.
- 3. Restricted Rights: Use, duplication or disclosure by the United States government is subject to the restrictions as set forth in the Rights in Technical Data and Computer Software Clauses in DFARS 252.227-7013(c) (1) and FAR 52.227-19(c) (2) as applicable.

All other trademarks and copyrights are the property of their respective owners.